

View Online at <https://aerobasegroup.com/nsn/3445-00-079-0483>

Power Rating:

3.000 horsepower

Current Type:

Ac

Power Unit Type:

Electric motor

Operation Method:

Powered

Mounting Method:

Floor

Power Unit:

Included

Punch Quantity And Size:

4 1/4 in., 4 5/16 in., 4 3/8 in., 4 7/16 in., 4 1/2 in., 4 9/16 in., 4 5/8 in., 4 11/16 in., 4 3/4 in., 4 13/16 in., 4 7/8 in., 1 1 in., 4 1-5/16 in.

Die Quantity And Size:

4 9/32 in., 4 11/32 in., 3 13/32 in., 4 23/32 in., 4 25/32 in., 4 27/32 in., 4 29/32 in., 4 31/32 in., 4 1-1/32 in.

Voltage In Volts:

208.0

Phase:

Three

Special Features:

44 strokes per min; sgl punch, min 2 punch, 20 in. Deep throat; 1-1/16 in. Diameter holes in 5/8 in. Thk mild steel rated capacity; punches are rd shape; dies are rd shape; 1, rated shear capacity, 1/2 in. Plate, 5/8 x 6 in. Flate bar, 1-5/ in. Rd bar, 1/2 to 1-1/2 in. Sq bar, 4 x 4 x 1/2 in.

Sq cut, angles 3 x 3 x 5/16 in. Mitered angles; equipped w/90 degrees notcher, integral type, 5/16 in. Mild steel rated capacity, 2-3/4 in.

Maximum notching depth; equipped w/sq coper, integral type

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-k