

View Online at <https://aerobasegroup.com/nsn/3445-00-262-3820>

Power Rating:

2.000 horsepower

Power Unit Type:

Electric motor

Operation Method:

Powered

Mounting Method:

Floor

Power Unit:

Included

Punch Quantity And Size:

4 1/4 in., 4 5/16 in., 4 3/8 in., 4 7/16 in., 4 1/2 in., 4 9/16 in., 4 5/8 in., 4 3/4 in., 4 7/8 in.

Die Quantity And Size:

4 1/4 in., 4 5/16 in., 4 3/8 in., 4 7/16 in., 4 1/2 in., 4 9/16 in., 4 3/4 in., 4 7/8 in.

Voltage In Volts:

208.0

Phase:

Three

Special Features:

Multiple punch, min 2 punch stations, 12 in. Deep throat, 13/16 in. Diameter hole in 7/16 in. Thk mild steel rated capacity, punches are round shape; dies are round shape; 1 shear, rated capacity, 3/8 in. Plate, 1/2 by 4 in. Flat bar, 1-1/4 in. Rd bar, 1/8 in. Sq bar, 3 x 3 x 3/8 in. Sq cut, angles 2 x 2 x 5/16 in. In mitered angles; equipped w/90 degrees notcher, integral type, 1/4 in. Mild steel rated capacity, 1-7/8 in. Maximum notching depth; equipped w/sq roper, integral type, 2 in. W, 1/4 in. Mild steel rated capacity, 2-3/4 in. Maximum coping depth; no attachments or accessories; no special f

Frequency In Hertz:

60.0

Specification Or Standard:

1 size

Departure From Cited Designator:

Power data electric type 208v, punch data punches incl, dies incl

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-k