

View Online at <https://aerobasegroup.com/nsn/3445-00-461-3584>

Power Rating:

3.000 horsepower

Current Type:

Ac

Power Unit Type:

Electric motor

Operation Method:

Powered

Power Unit:

Included

Voltage In Volts:

220.0

Phase:

Three

Special Features:

30 tons maximum hydraulic pressure; 7 in. Lg bar shear blades; 1/2 in. Thk x 6 in. Lg maximum cuts; 3 in. W by 1/2 in. Thk maximum angle shear; 1/2 in. Thk by 0.875 in. Diameter hole maximum punching in mild steel, 4 in. Throat depth, 27 in. W maximum sheet capacity for punching; notcher-coper attachment designed fro 90 degrees notching; round lock ring grooved punches w/dies, 1 0.250 in., 1 0.312 in., 2 0.375 in.2 0.438 in., 2 0.500 in., 2 0.562 in., 2 0.625 in., 1 0.688 in., 1 0.750 in., 1 0.812 in., 1 0.875 in., 1 0.938 in., 1 1 in., 1 1.125 in., 1 1.250 in.

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by the item bar shear blade lg, elec power requirements, furnished attachment and size of punches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-k