

View Online at <https://aerobasegroup.com/nsn/3445-00-528-9783>

Power Rating:

3.000 horsepower

Current Type:

Ac

Power Unit Type:

Electric motor

Operation Method:

Powered

Mounting Method:

Floor

Power Unit:

Included

Punch Quantity And Size:

1 1/2 in., 1 3/4 in.

Die Quantity And Size:

1 1/2 in., 1 3/4 in.

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

44 strokes per min.; sgl punch, 20 in. Deep throat, 1-1/16 in. Min diameter hole in 5/8 in. Thk mild steel rated capacity, punch shape round; dies punch shape round, 2 shears rated capacity, 1/2 in. Plate, 1-5/8 in. Rd bar, 1-1/2 in. Sq bar, 4 x 4 x 1/2 in. Straight angle, 3 x 3 x 5/16 in. Mitered angle; equipped w/90 degrees notcher, integral type, 5/16 in. Mild steel rated capacity, 2-3/4 in. Notching depth; equipped w/sq copper, integral type, 2 in. W, 3/8 in. Mild steel rated capacity, 3 in. Maximum coping depth; accessories: shear blades 2, std bar cutter 5, knife set, knives 1, knife set, notcher 3; no special features

Frequency In Hertz:

60.0

Specification Or Standard:

3 size

Departure From Cited Designator:

Equipped w/90 degrees notcher

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-k