

View Online at <https://aerobasegroup.com/nsn/3460-00-243-9607>

Current Type:

Ac

Carrying Case:

Provided

Motor Environmental Protection:

Fungus resistant

Furnished Items And Quantity:

Tee bolt 1, spindle oil can 1, diamond dresser 1, 3/4 by 1/2 by 1/4 in. Standard grinding wheel 1, 1 by 1/4 by 1/4 in. Standard grinding wheel 1, 1-1/2 by 1/4 by 1/4 in. Standard grinding wheel 1, 2 by 3/8 by 3/8 in. Standard grinding wheel 1, 3 by 1/2 by 3/8 in. Standard grinding wheel 1, 4 by 1/2 by 3/8 in. Standard grinding wheel 1, 5 by 1/2 by 3/8 in. Standard grinding wheel 1, 1/4 by 1/4 by 1/8 in mounted grinding wheel 1, 5/8 by 3/8 by 1/8 in. Mounted grinding wheel 1, 3/4 by 1/2 by 1/4 in. Mounted grinding wheel 1, 1-1/4 by 1/4 by 1/4 in. Mounted grinding wheel 1, wrench set 1

Plug Type:

3-prong polarized

Design Type:

Precision

Electric Motor Horsepower Rating:

0.50

Mounting Type For Which Designed:

Tool carriage

Spindle Speed In Rpm:

4350.0

Maximum Wheel Diameter Accommodated:

5.000 inches

Maximum Wheel Thickness Accommodated:

0.500 inches

Feed Position:

Vertical

Wheel Spindle Drive Type:

Belt

Spindle Type:

Quill

Motor Radio Interference Suppression:

Included

Electric Extension Cable/plug:

Included

Cord Length:

8.000 feet

Instruction Handbook Quantity:

2

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Frequency In Hertz:

60.0

Specification Or Standard:

1 type and 12 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T284-k