NSN 3460-00-516-4610

Machine Tool Attachment Grinding Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3460-00-516-4610 **Current Type:** Ac or dc **Carrying Case:** Provided **Motor Environmental Protection:** Fungus resistant **Furnished Items And Quantity:** Any acceptable Plug Type: 3-prong polarized **Design Type:** Precision **Electric Motor Horsepower Rating:** 0.25 **Mounting Type For Which Designed:** Tool carriage Spindle Speed In Rpm: Between 6600.0 and 38000.0 **Maximum Wheel Diameter Accommodated:** 3.000 inches **Maximum Wheel Thickness Accommodated:** 0.375 inches **Feed Position:** Horizontal Wheel Spindle Drive Type: Belt Spindle Type: Integral arbor **Motor Radio Interference Suppression:** Included **Electric Extension Cable/plug:** Included **Cord Length:** 8.000 feet **Instruction Handbook Quantity:** Voltage In Volts: 115.0 Phase: Single

Frequency In Hertz: 60.0

NSN 3460-00-516-4610

Machine Tool Attachment Grinding Machine - Page 2 of 2



| Specification Or Standard: |
|----------------------------|
| 10 size and i type |
| Shelf Life: |
| N1/ |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T284-k