

View Online at <https://aerobasegroup.com/nsn/3460-00-821-5908>

**General Description:**

Basic power unit data, any acceptable, electric motor data, ac, 1/3 hp, 208 v, 3 phase, 60 cycles, additional equipment furnished, 1 adapter, base, universal carriage bridge, 1 adapter, compound slide, 1 adapter, no. 2, asa machine taper shank, 1 adapter, no. 5 or no. 7 brown and sharpe taper shank, 1 arbor, angle mill, threaded, rh, 3/8-24 nf, 1 arbor, fly cutter, 45 degrees and 90 degrees cutter position, w/1/4 in. Min sq cutter bit, 1 arbor, shell end mil, 1/2 in., 1 arbor, side mil, w/1/8 and 3/8 in. Spacing collars and nuts, for 7/8 in. Bore cutters, 1 arbor, side mill, w/1/8 and 3/8 in. Spacing collars and nuts, for 1 in. Bore cutters, 1 arbor, side mill, w/3-1/2 in. Min mandrel, w/1/8 in., 3/16 in., 1/4 in., 1/2 in., 3/4 in., and 1-1/4 in. Spacing collars and nuts, for 7/8 in. Bore cutters, 1 arbor, w/0 to 1/2 in. Capacity chuck, 1 belt set, driving, 1 collet arbor, 1/4 in. Straight shank or setscrew arbor, 1 collet arbor, 3/8 in. Straight shank shank or setscrew arbor, 1 collet arbor, 1/2 in. Straight shank or setscrew arbor, 1 cutte

**Specification Or Standard:**

1 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A23900