

View Online at <https://aerobasegroup.com/nsn/3805-01-518-1589>

Wheel Quantity:

4

Prime Mover Type:

Diesel engine

Safe Operating Load Rating:

1066.0 kilograms

Design Type:

Verticle lift front dump

Engine Model Number:

Bf4m1011f

Engine Manufacturer Name:

Deutz

Bucket Width:

1730.0 millimeters

Bucket Type:

Standard

Closed Cab:

Included

Speed Range:

+0.0/+13.6 kilometers per hour

Special Features:

operation height fully raised 4140 mm; height ot hinge pin fully raised 3118 mm; height 2013 mm; ground clearance between wheels 222 mm; length with bucket 3531 mm; length less bucket 2712 mm; wheel base 1219 mm; dump reach 807 mm; rollback at ground 30 deg; dump angle 40 deg; width, tires standard 12.00 x 16.5 equals 1683 mm; clearance circle-rear 1626 mm; clearance circle-front less bucket 1295 mm; clearance cirle front with bucket 2159 mm; seat to ground height 959 mm; rollback at full height 97 deg; dump height 2381 mm; departure angle 25 deg; operating weight 3341 kg; tip capaci type 2132 kg; breakout force 2136 kg

Supplementary Features:

Hydraulic loader circuit pump 76/125 dec l/min; loader circuit pressure 193 bar; hydraulic reservoir 611; utility bucket 1830 mm; lightmaterial bucket 1830 mm; backhoe attachment loading height 2450 mm; reach from pivot 3900 mm; digging depth 3050 mm; engine power output maximum 80 ps; at rpm 2650 u/min; cylinder/displacement 4/2910 qcm; fuel capaci type 911

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T334-f