NSN 3810-01-067-3991

Wheel Mounted Crane - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3810-01-067-3991

| Steerable Wheel Quantity: |
|--|
| 4 |
| Furnished Items And Quantity: |
| Lamshell 1 |
| Operation Method: |
| Power |
| Boom Design: |
| Telescoping |
| Wheel Arrangement Style: |
| Single wheels, single axle each end |
| Drum Quantity: |
| 1 |
| Maximum Lifting Capacity: |
| 7.5 tons |
| Boom Length At Which Lifting Capacity Is Rated: |
| Between 21.000 feet and 40.000 feet |
| Boom Radius At Which Lifting Capacity Is Rated: |
| 35.000 feet |
| Outrigger Position At Which Lifting Capacity Is Rated: |
| Set |
| Boomlength: |
| Between 21.000 feet and 40.000 feet |
| Boom Maximum Angle In Deg: |
| 360.0 |
| Boom Continuous Rotation Feature: |
| Included |
| Boom Maximum Rotation In Deg: |
| 360.0 |
| Boom Extension Type: |
| Telescopic |
| Rear Drive Wheel Quantity: |
| 2 |
| Front Drive Wheel Quantity: |
| 2 |
| Outriggers: |
| Included |
| Pile Driver: |
| Not included |
| Crane Operator Cab: |
| Included |
| Operating Power Type: |
| Hydraulic |

NSN 3810-01-067-3991

Wheel Mounted Crane - Page 2 of 2



4 cylinder diesel engine; 12 vdc; material - steel

Reference Data And Literature:

T.O. 36a12-22-4-1

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

T340-a