NSN 3810-01-130-6415

Wheel Mounted Crane - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3810-01-130-6415

| Steerable Wheel Quantity: |
|--|
| 4 |
| Operation Method: |
| Power |
| Boom Design: |
| Telescoping |
| Wheel Arrangement Style: |
| Dual wheels, single axle at each end |
| Drum Quantity: |
| 2 |
| Maximum Lifting Capacity: |
| 50.0 tons |
| Boom Length At Which Lifting Capacity Is Rated: |
| 38.000 feet |
| Boom Radius At Which Lifting Capacity Is Rated: |
| Between 10.000 feet and 115.000 feet |
| Outrigger Position At Which Lifting Capacity Is Rated: |
| Set |
| Boomlength: |
| 115.000 feet |
| Boom Maximum Angle In Deg: |
| 72.0 |
| Boom Continuous Rotation Feature: |
| Included |
| Rear Drive Wheel Quantity: |
| 4 |
| Outriggers: |
| Included |
| Pile Driver: |
| Not included |
| Crane Operator Cab: |
| Included |
| Operating Power Type: |
| Hydraulic |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

T340-a