

View Online at <https://aerobasegroup.com/nsn/3810-01-576-5917>

Prime Mover Type:

Diesel engine

Operation Method:

Power

Boom Design:

Telescoping

Maximum Lifting Capacity:

165.0 tons

Boomlength:

Between 42.000 feet and 167.000 feet

Boom Maximum Angle In Deg:

83.0

Outriggers:

Included

Crane Operator Cab:

Not included

Special Features:

Boom full pwr, has quick reeve nose, 5 sections; rem aux boom nose w/rem pin type rope guard, w/sgl lift cyl w/saftey valve, angle -3 degrees to 83 deg; load moment & anti 2 blk sys; cap equip w/acoustical lining, tinted saftey glass, adj operator seat, opening side & rear windows, hinged ft window w/wiper & shade; full electronic cntl of crane movement using electrical control movement auto reset to 0; min 88, 400lbs cwtw/hydr installation/cab removal; dual thermo conrolled oil coolers; elec sys 3 phase altnt, 28v/80amps dc, 2 batteries 12v/170a mp hour dc; chassis bx type torsion resistant frame high str steel; 4 hydr sgl stg outrigger beams w/vertical cyl pads; fuel tk min106 gl; elek pneu shift; dr steer arr 10x6x10; dr axle w/planetary hub rdcn & ctr mount diff gearig; inter & cross axle diff locks; indep hydro-pneu sys on wheels; 2 man caba/c & heat

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T340-a