## NSN 3895-00-053-0388

Bitumen Heating Kettle - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3895-00-053-0388 **Mounting Type:** Wheel Media For Which Designed: Fuel oil and kerosene Wheel Quantity: **Furnished Items And Quantity:** Automatic temperature control unit 1, dial-type bimettalic thermometer 1, hand spray bar 1, hose, insulated flexible spray 1 Tire Type: Pneumatic **Horsepower Rating:** 2.0 **Heating Method:** Direct **Resilient Joint Sealing Compound Design Feature:** Not included **Burner Quantity: Insulated Tank:** Not included **Loading Height:** 48.000 inches Loading Lid Quantity: **Loading Lid Type:** Hinged **Bitumen Agitator:** Not included **Bitumen Discharging Method:** Positive displacement pump **Discharge Capacity:** 18.0 gallons per minute **Bitumen Discharge Power Source:** Gasoline engine **Paving Hand Tool Heating Feature:** Not included Capacity:

165.0 gallons

**Specification Or Standard:** 

165 gal size

**Departure From Cited Designator:** 

Miprs mp-3-00924, mp-3-00978, and mp-3-01001

## NSN 3895-00-053-0388

Bitumen Heating Kettle - Page 2 of 2



| _ |    |      |   |        |  |
|---|----|------|---|--------|--|
| c | hο | JIF. |   | .ife:  |  |
| J |    |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T209-I