

View Online at <https://aerobasegroup.com/nsn/3895-00-063-6049>

**Mounting Type:**

Wheel

**Media For Which Designed:**

Liquefied petroleum gas

**Wheel Quantity:**

2

**Furnished Items And Quantity:**

Hand operated sealer bar 1, sealer bar nozzles 0.115 in. W 3, sealer bar nozzles 0.180 in. W 3, sealer bar nozzles 0.500 in. W 3

**Tire Type:**

Pneumatic

**Horsepower Rating:**

18.0

**Operation Method:**

Power

**Heating Method:**

Indirect

**Resilient Joint Sealing Compound Design Feature:**

Included

**Burner Quantity:**

3

**Insulated Tank:**

Included

**Loading Height:**

54.000 inches

**Loading Lid Quantity:**

1

**Loading Lid Type:**

Hinged

**Bitumen Agitator:**

Included

**Bitumen Discharging Method:**

Positive displacement pump

**Discharge Capacity:**

35.0 gallons per minute

**Bitumen Discharge Power Source:**

Liquid petroleum gas engine

**Paving Hand Tool Heating Feature:**

Not included

**Capacity:**

100.0 gallons

**Specification Or Standard:**

1 type

**Reference Number Differentiating Characteristics:**

As differentiated by burner quantity, media for which designed, bitumen discharge power source

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T209-I