

View Online at https://aerobasegroup.com/nsn/3895-00-187-6579

| view Online at https://aerobasegroup.com/hsr/3093-00-107-0379 |
|---|
| Mounting Provision: |
| Unthreaded mounting holes |
| Bore Diameter: |
| 5.000 inches |
| First End Hole Diameter: |
| 2.000 inches |
| Compressed Length: |
| 43.000 inches |
| Extended Length: |
| 73.500 inches |
| Mounting Provision Arrangement Style: |
| Two hole |
| Integral Valve Operation Method: |
| Pneumatic |
| Design Characteristics: |
| Double acting single cylinder |
| First Piston Rod End Style: |
| Ring type |
| Mounting Type And Location: |
| Tongue piston rod end |
| Mounting Facility Diameter: |
| 2.000 inches |
| Center To Center Distance Between Mounting Provisions: |
| 43.000 inches |
| Port Location And Quantity: |
| 1 piston rod end |
| Port Style: |
| Gasket seal |
| Port Thread Series Designator: |
| Unf |
| Port Thread Diameter: |
| 1.062 inches |
| Port Thready Qty Per Inch (tpi): |
| 12 |
| Port Thread Class: |
| 2a |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 3895-00-187-6579

Linear Actuating Cylinder Assembly - Page 2 of 2

Fiig: A34200

