

View Online at <https://aerobasegroup.com/nsn/3895-00-247-7480>

**Design Type:**

Towed

**Special Features:**

Paver, asphalt, towed type; three ton cap storage hopper, back of hopper shall not exceed 33-1/2 in. H, hopper mtd on 2 sets of dual tandem pneumaticrubber tires/8tires/5.30 by 6, 6 ply, mtd in line, 2 tires in front & 2 directly behind, that are walking-beam supp toan adj undercarriage frame, prov 4 diff h settings, paver shall be cap of laying asphalt from a min depth, determined by the size of aggregate in the mix, to a maximum of 6 in. In asphalt, by adj the undercarriage frame to its maximum h., the paver shall be cap of spreading mat. To a maximum depth of 10 in., w/3 sets of ditch plates, spread w., o-42 in., 28-76 in., & 62-110 in., w/heated screed, complete w/propane tank, reg and gauge, w/elec power hyd sys, w/battery, w/diesel sprayer, designed for towing or transp from tail-gate of dump-truck, hooks and chain furnished, w/hyd oper hook-up, paver shall be furnished w/all necessary equip to make a complete item

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T209-q