## NSN 3895-00-540-6657

Bitumen Heating Kettle - Page 1 of 2

1 type



View Online at https://aerobasegroup.com/nsn/3895-00-540-6657
Mounting Type:
Wheel
Media For Which Designed:
Liquefied petroleum gas
Wheel Quantity:
2
Furnished Items And Quantity:
Applicator hose 1, applicator nozzles 1/8 in., 3, applicator nozzles 1/4 in. 3, applicator nozzles 1/2 in., 3 pressure regulators and hose 1 set,
suction hose 1, tarpulin 1
Tire Type:
Pneumatic
Horsepower Rating:
12.0
Operation Method:
Power
Heating Method:
Indirect
Resilient Joint Sealing Compound Design Feature:
Included
Burner Quantity:
2
Insulated Tank:
Included
Loading Height:
65.000 inches
Loading Lid Quantity:
1
Loading Lid Type:
Hinged
Bitumen Agitator:
Included
Bitumen Discharging Method:
Positive displacement pump
Discharge Capacity:
35.0 gallons per minute
Bitumen Discharge Power Source:
Liquid petroleum gas engine
Paving Hand Tool Heating Feature:
Not included
Capacity:
165.0 gallons
Specification Or Standard:

## NSN 3895-00-540-6657

Bitumen Heating Kettle - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T209-I