

View Online at <https://aerobasegroup.com/nsn/3895-00-803-3204>

Mounting Type:

Wheel

Media For Which Designed:

Kerosene

Wheel Quantity:

2

Furnished Items And Quantity:

Hand operated sealer bar 1, sealer bar nozzles 0.115 in. W 3, sealer bar nozzles 0.180 in. W 3, sealer bar nozzles 0.500 in. W 3

Tire Type:

Pneumatic

Horsepower Rating:

18.0

Operation Method:

Power

Heating Method:

Indirect

Resilient Joint Sealing Compound Design Feature:

Included

Burner Quantity:

2

Insulated Tank:

Included

Loading Height:

54.000 inches

Loading Lid Quantity:

1

Loading Lid Type:

Hinged

Bitumen Agitator:

Included

Bitumen Discharging Method:

Positive displacement pump

Discharge Capacity:

35.0 gallons per minute

Bitumen Discharge Power Source:

Gasoline engine

Paving Hand Tool Heating Feature:

Not included

Capacity:

100.0 gallons

Specification Or Standard:

2 type

Reference Number Differentiating Characteristics:

As differentiated by burner quantity, media for which designed, bitumen discharge power source

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T209-I