## NSN 3895-00-815-9357

Bitumen Heating Kettle - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3895-00-815-9357

Mounting Type:
Wheel
Media For Which Designed:
Liquefied petroleum gas
Wheel Quantity:
2
Furnished Items And Quantity:
Hand operated sealer bar 1, sealer bar nozzles 0.115 in. W 3, sealer bar nozzles 0.180 in. W 3, sealer bar nozzles 0.250 in. W 3
Tire Type:
Pneumatic
Horsepower Rating:
13.5
Operation Method:
Power
Heating Method:
Indirect
Resilient Joint Sealing Compound Design Feature:
Included
Burner Quantity:
2
Insulated Tank:
Included
Loading Height:
60.000 inches
Loading Lid Quantity:
1
Loading Lid Type:
Hinged
Bitumen Agitator:
Included
Bitumen Discharging Method:
Positive displacement pump
Discharge Capacity:
35.0 gallons per minute
Bitumen Discharge Power Source:
Liquid petroleum gas engine
Paving Hand Tool Heating Feature:
Not included
Capacity:
100.0 gallons
Specification Or Standard:

1 type

## NSN 3895-00-815-9357

Bitumen Heating Kettle - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T209-I