NSN 3895-00-945-6718

Bitumen Heating Kettle - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3895-00-945-6718

The state of the s
Mounting Type:
Wheel
Media For Which Designed:
Liquefied petroleum gas
Wheel Quantity:
2
Furnished Items And Quantity:
Hand operated sealing bar 1, sealed bar nozzles 0.115 in. W 3, sealed bar nozzles 0.180 in. W 3, sealed bar nozzles 0.500 in. W 3
Tire Type:
Pneumatic
Horsepower Rating:
18.0
Operation Method:
Power
Heating Method:
Indirect
Resilient Joint Sealing Compound Design Feature:
Included
Burner Quantity:
3
Insulated Tank:
Included
Loading Height:
54.000 inches
Loading Lid Quantity:
1
Loading Lid Type:
Hinged
Bitumen Agitator:
Included
Bitumen Discharging Method:
Positive displacement pump
Discharge Capacity:
35.0 gallons per minute
Bitumen Discharge Power Source:
Liquid petroleum gas engine
Paving Hand Tool Heating Feature:
Not included
Capacity:
100.0 gallons
Special Features

Desinged for heated hose compartment to be added to eliminate freezing of sealer hose

NSN 3895-00-945-6718

Bitumen Heating Kettle - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.II C	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T209-I