

View Online at <https://aerobasegroup.com/nsn/3895-01-067-1651>

**Media For Which Designed:**

Diesel oil and kerosene

**Furnished Items And Quantity:**

Lighting torch, spray tube, spray nozzles, 1 in. By 15 ft hose

**Horsepower Rating:**

8.0

**Heating Method:**

Indirect

**Resilient Joint Sealing Compound Design Feature:**

Not included

**Burner Quantity:**

1

**Insulated Tank:**

Included

**Loading Height:**

66.000 inches

**Loading Lid Quantity:**

1

**Loading Lid Type:**

Hinged

**Bitumen Agitator:**

Not included

**Bitumen Discharging Method:**

Positive displacement pump

**Discharge Capacity:**

18.0 gallons per minute

**Bitumen Discharge Power Source:**

Gasoline engine

**Paving Hand Tool Heating Feature:**

Not included

**Capacity:**

165.0 gallons

**Special Features:**

Melting pot is 10 ga. Steel with splash guard; fire box is 12 ga. Steel; frame is 4 in. Channel-reinforced; the burner system is bottom fired, has 2 liquid propane fired burner (500, 000 btu ea.) with necessary piping, safety shut-down valve, I.P. Bottle rack, regulator, hose and tank fitting to ready unit for operation; contains 5/16 in. Safety chain w/hooks and latches, paint, 3 in. Dial thermometer, 5, 000 lb. Screw jack, ring hitch, 16 ga. Steel smoke stack

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T200.L