

View Online at <https://aerobasegroup.com/nsn/3895-01-067-1651>

Media For Which Designed:

Diesel oil and kerosene

Furnished Items And Quantity:

Lighting torch, spray tube, spray nozzles, 1 in. By 15 ft hose

Horsepower Rating:

8.0

Heating Method:

Indirect

Resilient Joint Sealing Compound Design Feature:

Not included

Burner Quantity:

1

Insulated Tank:

Included

Loading Height:

66.000 inches

Loading Lid Quantity:

1

Loading Lid Type:

Hinged

Bitumen Agitator:

Not included

Bitumen Discharging Method:

Positive displacement pump

Discharge Capacity:

18.0 gallons per minute

Bitumen Discharge Power Source:

Gasoline engine

Paving Hand Tool Heating Feature:

Not included

Capacity:

165.0 gallons

Special Features:

Melting pot is 10 ga. Steel with splash guard; fire box is 12 ga. Steel; frame is 4 in. Channel-reinforced; the burner system is bottom fired, has 2 liquid propane fired burner (500, 000 btu ea.) with necessary piping, safety shut-down valve, I.P. Bottle rack, regulator, hose and tank fitting to ready unit for operation; contains 5/16 in. Safety chain w/hooks and latches, paint, 3 in. Dial thermometer, 5, 000 lb. Screw jack, ring hitch, 16 ga. Steel smoke stack

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T200.L