

View Online at <https://aerobasegroup.com/nsn/3895-01-068-3062>

Mounting Type:

Wheel

Media For Which Designed:

Light fuel oil and kerosene

Wheel Quantity:

2

Furnished Items And Quantity:

Tube 1.75 in. Thinwall 20 ft lg w/knock-on unions 5, tube 2 in. Thinwall 10 ft lg w/1.5 in. Welded-on nipple ea end 3, tube 2 in. Thinwall 6 ft lg w/1.5 in. Welded-on nipple ea end 1, tube 2 in. Thinwall 4 ft lg w/1.5 in. Welded-on nipple ea end 1, 1.5 in. Knock-on unions 4, swivel connector 2, stinger nozzle 2

Tire Type:

Pneumatic

Horsepower Rating:

10.0

Operation Method:

Power

Heating Method:

Indirect

Resilient Joint Sealing Compound Design Feature:

Not included

Burner Quantity:

1

Insulated Tank:

Included

Loading Height:

Between 40.000 inches and 46.000 inches

Loading Lid Quantity:

2

Loading Lid Type:

Hinged

Bitumen Agitator:

Included

Bitumen Discharging Method:

Positive displacement pump

Discharge Capacity:

50.0 gallons per minute

Bitumen Discharge Power Source:

Gasoline engine

Paving Hand Tool Heating Feature:

Not included

Capacity:

360.0 gallons

Specification Or Standard:

165 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T209-I