## NSN 3910-00-298-9630

Belt Conveyor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3910-00-298-9630

| Overall Length:                             |  |  |  |  |
|---|--|--|--|--|
| 35.000 feet                                 |  |  |  |  |
| Overall Width:                              |  |  |  |  |
| 95.500 inches                               |  |  |  |  |
| Portability Method:                         |  |  |  |  |
| Wheels                                      |  |  |  |  |
| Tire Type:                                  |  |  |  |  |
| Metal                                       |  |  |  |  |
| Installation Design:                        |  |  |  |  |
| Portable                                    |  |  |  |  |
| Operation Method:                           |  |  |  |  |
| Power                                       |  |  |  |  |
| Manufacturer Name:                          |  |  |  |  |
| Any acceptable                              |  |  |  |  |
| Belt Width:                                 |  |  |  |  |
| 30.000 inches                               |  |  |  |  |
| Belt Length:                                |  |  |  |  |
| 75.000 feet                                 |  |  |  |  |
| Engine Model Number:                        |  |  |  |  |
| Any acceptable                              |  |  |  |  |
| Power Source:                               |  |  |  |  |
| Gasoline engine                             |  |  |  |  |
| Capacity Rating:                            |  |  |  |  |
| 450.0 tons per hour                         |  |  |  |  |
| Brake Horsepower At Specificationified Rpm: |  |  |  |  |
| 17 bhp at2000 rpm                           |  |  |  |  |
| Maximum Load Rating:                        |  |  |  |  |
| 50.000 pounds per foot                      |  |  |  |  |
| Self-propelled Feature:                     |  |  |  |  |
| Not included                                |  |  |  |  |
| Belt Speed:                                 |  |  |  |  |
| 300.000 feet per minute                     |  |  |  |  |
| Power Unit:                                 |  |  |  |  |
| Included                                    |  |  |  |  |
| Load Delivery Height:                       |  |  |  |  |
| Between 4.500 feet and 13.000 feet          |  |  |  |  |
| Belt Material:                              |  |  |  |  |
| Cotton duck                                 |  |  |  |  |
| Belt Carrying Cleats:                       |  |  |  |  |
| Not included                                |  |  |  |  |
| Belt Guide Type:                            |  |  |  |  |
| Trough rollers                              |  |  |  |  |

## NSN 3910-00-298-9630

Belt Conveyor - Page 2 of 2



| Reference | Number   | Differentiating  | Characteristics:    |
|-----------|----------|------------------|---------------------|
|           | MUIIINEI | Dillelelluatilly | Cital actel istics. |

Low mast and pacs afjs, atyx, bgsg, abhp, bgsk, arfy

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T211-a