

View Online at <https://aerobasegroup.com/nsn/3930-00-165-4152>

Hazardous Locations/environmental Protection:

U.L. Type g

Overall Width:

54.500 inches

Fork Length:

36.000 inches

Fork Width:

6.000 inches

Overall Height With Forks In Lowest Position:

91.000 inches

Overall Height With Forks In Highest Position:

216.000 inches

Overall Length Without Forks:

112.500 inches

Vehicular Turn Radius:

104.000 inches

Fork Load Center Distance:

24.000 inches

Lift Mechanism Type:

Hydraulic

Lift Actuation Method:

Powered

Prime Mover Type:

Gasoline engine

Transmission Type:

Automatic

Maximum Load Rating:

6000.000 pounds

Features Provided:

Nontactical electromagnetic interference suppression and telescopic mast

Wheel Type And Quantity:

2 single pneumatic steerable wheel

Lift Height Of Forks:

168.000 inches

Boom Forward Tilt Angle:

3.0 degrees

Prime Mover Manufacturer Code And Model Number:

02978-f245

Boom Backward Tilt Angle:

10.0 degrees

Fork Spread Distance:

Between 12.000 inches and 48.000 inches

Special Features:

12 vdc; 6 cylinder

Entry Date:

89-10-01

Reference Data And Literature:

Mil-hdbk-300; t.O. 36m2-2-95-73

Style Designator:

Conventional

Reference Number Differentiating Characteristics:

As differentiated by model year 1972

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A085a0

Mil-std (military Standard):

spec.