

View Online at <https://aerobasegroup.com/nsn/3930-00-165-4152>

**Hazardous Locations/environmental Protection:**

U.L. Type g

**Overall Width:**

54.500 inches

**Fork Length:**

36.000 inches

**Fork Width:**

6.000 inches

**Overall Height With Forks In Lowest Position:**

91.000 inches

**Overall Height With Forks In Highest Position:**

216.000 inches

**Overall Length Without Forks:**

112.500 inches

**Vehicular Turn Radius:**

104.000 inches

**Fork Load Center Distance:**

24.000 inches

**Lift Mechanism Type:**

Hydraulic

**Lift Actuation Method:**

Powered

**Prime Mover Type:**

Gasoline engine

**Transmission Type:**

Automatic

**Maximum Load Rating:**

6000.000 pounds

**Features Provided:**

Nontactical electromagnetic interference suppression and telescopic mast

**Wheel Type And Quantity:**

2 single pneumatic steerable wheel

**Lift Height Of Forks:**

168.000 inches

**Boom Forward Tilt Angle:**

3.0 degrees

**Prime Mover Manufacturer Code And Model Number:**

02978-f245

**Boom Backward Tilt Angle:**

10.0 degrees

**Fork Spread Distance:**

Between 12.000 inches and 48.000 inches

**Special Features:**

12 vdc; 6 cylinder

**Entry Date:**

89-10-01

**Reference Data And Literature:**

Mil-hdbk-300; t.O. 36m2-2-95-73

**Style Designator:**

Conventional

**Reference Number Differentiating Characteristics:**

As differentiated by model year 1972

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A085a0

**Mil-std (military Standard):**

spec.