NSN 3930-00-200-8113

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3930-00-200-8113 **Body Material:** Any acceptable First End Outside Diameter: 1.500 inches **Mounting Provision:** Pin **Tempurature Rating:** -10.0 degrees fahrenheit **Mounting Facility Length:** 2.062 inches **Overall Height:** 5.000 inches **Overall Width:** 4.000 inches **Bore Diameter:** 3.500 inches Seat Angle In Deg: Any acceptable First End External Thread Length: 3.250 inches **Compressed Length:** 18.250 inches **Extended Length:** 24.000 inches **Pressure Rating:** 1000.0 pounds per square inch **Integral Valve Operation Method:** Mechanical **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: First Piston Rod End Thread Series Designator: First Piston Rod End Thready Qty Per Inch (tpi):

External threaded Unf First Piston Rod End Thread Diameter: 1.500 inches 12 First Piston Rod End Thread Class: 2a **First Piston Rod End Thread Direction:** Right-hand

NSN 3930-00-200-8113

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Type And Location:
Trunnion cylinder head end
Mounting Facility Diameter:
0.875 inches
Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Nptf
Port Thread Diameter:
0.375 inches
Port Pipe Thread Size:
0.375 inches
Special Features:
0.344 in. Holes drilled in ea end of trunnion
Fsc Application Data:
Truck, lift, fork
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200