NSN 3930-00-222-8255

Fork Lift Truck - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3930-00-222-8255

| Hazardous Locations/environmental Protection: | | | | | | |
|--|--|--|--|--|--|--|
| U.L. Type g | | | | | | |
| Fork Length: | | | | | | |
| 40.000 inches | | | | | | |
| Fork Width: | | | | | | |
| 5.000 inches | | | | | | |
| Overall Height With Forks In Lowest Position: | | | | | | |
| 68.000 inches | | | | | | |
| Overall Height With Forks In Highest Position: | | | | | | |
| 192.000 inches | | | | | | |
| Storage Aisle Minimum Width: | | | | | | |
| 180.000 inches | | | | | | |
| Fork Load Center Distance: | | | | | | |
| 24.000 inches | | | | | | |
| Fork/platform Maximum Free Lift Height: | | | | | | |
| 44.000 inches | | | | | | |
| Lift Mechanism Type: | | | | | | |
| Hydraulic | | | | | | |
| Lift Actuation Method: | | | | | | |
| Powered | | | | | | |
| Prime Mover Type: | | | | | | |
| Gasoline engine | | | | | | |
| Transmission Type: | | | | | | |
| Automatic | | | | | | |
| Maximum Load Rating: | | | | | | |
| 4000.000 pounds | | | | | | |
| Features Provided: | | | | | | |
| Nontactical electromagnetic interference suppression | | | | | | |
| Wheel Type And Quantity: | | | | | | |
| 2 dual pneumatic steerable wheel | | | | | | |
| Lift Height Of Forks: | | | | | | |
| 144.000 inches | | | | | | |
| Boom Forward Tilt Angle: | | | | | | |
| 2.0 degrees | | | | | | |
| Boom Backward Tilt Angle: | | | | | | |
| 6.0 degrees | | | | | | |
| Fork Spread Distance: | | | | | | |
| Between 10.000 inches and 32.000 inches | | | | | | |
| Specification Or Standard: | | | | | | |
| G type | | | | | | |
| Shelf Life: | | | | | | |
| N/a | | | | | | |

NSN 3930-00-222-8255Fork Lift Truck - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

Demilitarization:

No

Fiig:

A085a0