NSN 3930-00-679-4457

Hazardous Locations/environmental Protection:

Fork Lift Truck - Page 1 of 2

U.L. Type g



View Online at https://aerobasegroup.com/nsn/3930-00-679-4457

Overall Width:
53.000 inches
Fork Length:
40.000 inches
Fork Width:
7.000 inches
Overall Height With Forks In Lowest Position:
68.000 inches
Overall Length Without Forks:
101.250 inches
Fork Load Center Distance:
24.000 inches
Fork/platform Maximum Free Lift Height:
43.000 inches
Lift Mechanism Type:
Hydraulic
Lift Actuation Method:
Powered
Prime Mover Type:
Gasoline engine
Transmission Type:
Transmission Type: Automatic
Automatic
Automatic Maximum Load Rating:
Automatic Maximum Load Rating: 10000.000 pounds
Automatic Maximum Load Rating: 10000.000 pounds Features Provided:
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression Wheel Type And Quantity:
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression Wheel Type And Quantity: 2 dual solid drive wheel
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression Wheel Type And Quantity: 2 dual solid drive wheel Lift Height Of Forks:
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression Wheel Type And Quantity: 2 dual solid drive wheel Lift Height Of Forks: 100.000 inches
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression Wheel Type And Quantity: 2 dual solid drive wheel Lift Height Of Forks: 100.000 inches Boom Forward Tilt Angle:
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression Wheel Type And Quantity: 2 dual solid drive wheel Lift Height Of Forks: 100.000 inches Boom Forward Tilt Angle: 3.0 degrees
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression Wheel Type And Quantity: 2 dual solid drive wheel Lift Height Of Forks: 100.000 inches Boom Forward Tilt Angle: 3.0 degrees Prime Mover Manufacturer Code And Model Number:
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression Wheel Type And Quantity: 2 dual solid drive wheel Lift Height Of Forks: 100.000 inches Boom Forward Tilt Angle: 3.0 degrees Prime Mover Manufacturer Code And Model Number: 02978-f162-6048
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression Wheel Type And Quantity: 2 dual solid drive wheel Lift Height Of Forks: 100.000 inches Boom Forward Tilt Angle: 3.0 degrees Prime Mover Manufacturer Code And Model Number: 02978-f162-6048 Boom Backward Tilt Angle:
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression Wheel Type And Quantity: 2 dual solid drive wheel Lift Height Of Forks: 100.000 inches Boom Forward Tilt Angle: 3.0 degrees Prime Mover Manufacturer Code And Model Number: 02978-f162-6048 Boom Backward Tilt Angle: 10.0 degrees
Automatic Maximum Load Rating: 10000.000 pounds Features Provided: Nontactical electromagnetic interference suppression Wheel Type And Quantity: 2 dual solid drive wheel Lift Height Of Forks: 100.000 inches Boom Forward Tilt Angle: 3.0 degrees Prime Mover Manufacturer Code And Model Number: 02978-f162-6048 Boom Backward Tilt Angle: 10.0 degrees Fork Spread Distance:

NSN 3930-00-679-4457Fork Lift Truck - Page 2 of 2



She	lf	Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A085a0