## NSN 3930-00-792-8327

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3930-00-792-8327 **Body Material:** Any acceptable First End Outside Diameter: 3.000 inches **Mounting Provision:** Unthreaded mounting holes **Tempurature Rating:** -10.0 degrees fahrenheit **Overall Height:** 8.875 inches **Overall Width:** 6.250 inches **Bore Diameter:** 5.500 inches **Body Outside Diameter:** 6.250 inches **Mounting Facility Thread Direction:** Right-hand First End Hole Diameter: Unable to decode First End Thickness At Mounting Holes: 2.500 inches **Compressed Length:** 45.375 inches **Extended Length:** 77.500 inches **Mounting Provision Arrangement Style:** Two hole **Pressure Rating:** 1500.0 pounds per square inch **Mounting Facility Thread Series Designator: Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: Bearing type **Mounting Type And Location:** Bearing cylinder head end

**Mounting Facility Pipe Thread Size:** 0.750 inches

## NSN 3930-00-792-8327

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Facility Diameter:	
1.502 inches	
Center To Center Distance Between Mounting Provisions:	
1.500 inches	
Port Location And Quantity:	
1 piston rod end	
Port Style:	
Gasket seal	
Port Thread Series Designator:	
Nptf	
Port Thread Diameter:	
0.750 inches	
Port Pipe Thread Size:	
0.750 inches	
Special Features:	
Mtg facility has 3.000 in.Od, 8.875 in.Thk at mtg holes	
Fsc Application Data:	
Truck, lift, fork	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A34200	