

View Online at <https://aerobasegroup.com/nsn/3930-00-792-8327>

Body Material:

Any acceptable

First End Outside Diameter:

3.000 inches

Mounting Provision:

Unthreaded mounting holes

Temperature Rating:

-10.0 degrees fahrenheit

Overall Height:

8.875 inches

Overall Width:

6.250 inches

Bore Diameter:

5.500 inches

Body Outside Diameter:

6.250 inches

Mounting Facility Thread Direction:

Right-hand

First End Hole Diameter:

Unable to decode

First End Thickness At Mounting Holes:

2.500 inches

Compressed Length:

45.375 inches

Extended Length:

77.500 inches

Mounting Provision Arrangement Style:

Two hole

Pressure Rating:

1500.0 pounds per square inch

Mounting Facility Thread Series Designator:

Nptf

Integral Valve Operation Method:

Hydraulic

Design Characteristics:

Double acting single cylinder

First Piston Rod End Style:

Bearing type

Mounting Type And Location:

Bearing cylinder head end

Mounting Facility Pipe Thread Size:

0.750 inches

Mounting Facility Diameter:

1.502 inches

Center To Center Distance Between Mounting Provisions:

1.500 inches

Port Location And Quantity:

1 piston rod end

Port Style:

Gasket seal

Port Thread Series Designator:

Nptf

Port Thread Diameter:

0.750 inches

Port Pipe Thread Size:

0.750 inches

Special Features:

Mtg facility has 3.000 in.Od, 8.875 in.Thk at mtg holes

Fsc Application Data:

Truck, lift, fork

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A34200