NSN 3930-00-965-0140

Fork Lift Truck - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3930-00-965-0140

| Hazardous Locations/environmental Protection: |
|---|
| U.L. Type ee |
| Overall Width: |
| 42.000 inches |
| Fork Length: |
| 40.000 inches |
| Fork Width: |
| 5.000 inches |
| Overall Height With Forks In Lowest Position: |
| 91.000 inches |
| Battery Compartment Length: |
| 39.500 inches |
| Battery Compartment Width: |
| 31.750 inches |
| Battery Compartment Depth: |
| 25.000 inches |
| Vehicular Turn Radius: |
| 71.000 inches |
| Storage Aisle Minimum Width: |
| 144.000 inches |
| Fork Load Center Distance: |
| 24.000 inches |
| Fork/platform Maximum Free Lift Height: |
| |
| 57.000 inches |
| |
| 57.000 inches |
| 57.000 inches Lift Mechanism Type: |
| 57.000 inches Lift Mechanism Type: Hydraulic |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: Electric motor |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: Electric motor Maximum Load Rating: |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: Electric motor Maximum Load Rating: 4000.000 pounds |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: Electric motor Maximum Load Rating: 4000.000 pounds Features Provided: |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: Electric motor Maximum Load Rating: 4000.000 pounds Features Provided: Telescopic mast |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: Electric motor Maximum Load Rating: 4000.000 pounds Features Provided: Telescopic mast Wheel Type And Quantity: |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: Electric motor Maximum Load Rating: 4000.000 pounds Features Provided: Telescopic mast Wheel Type And Quantity: 2 dual solid steerable wheel |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: Electric motor Maximum Load Rating: 4000.000 pounds Features Provided: Telescopic mast Wheel Type And Quantity: 2 dual solid steerable wheel Lift Height Of Forks: |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: Electric motor Maximum Load Rating: 4000.000 pounds Features Provided: Telescopic mast Wheel Type And Quantity: 2 dual solid steerable wheel Lift Height Of Forks: 144.000 inches |
| 57.000 inches Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: Electric motor Maximum Load Rating: 4000.000 pounds Features Provided: Telescopic mast Wheel Type And Quantity: 2 dual solid steerable wheel Lift Height Of Forks: 144.000 inches Boom Forward Tilt Angle: |

NSN 3930-00-965-0140Fork Lift Truck - Page 2 of 2



| Fork Spread Distance: |
|---|
| Between 12.000 inches and 32.000 inches |
| Special Features: |
| Upright boom |
| Style Designator: |
| Conventional |
| Specification Or Standard: |
| E type and v size |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A085a0