## NSN 3930-00-965-0140

Fork Lift Truck - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3930-00-965-0140

Hazardous Locations/environmental Protection:
U.L. Type ee
Overall Width:
42.000 inches
Fork Length:
40.000 inches
Fork Width:
5.000 inches
Overall Height With Forks In Lowest Position:
91.000 inches
Battery Compartment Length:
39.500 inches
Battery Compartment Width:
31.750 inches
Battery Compartment Depth:
25.000 inches
Vehicular Turn Radius:
71.000 inches
Storage Aisle Minimum Width:
144.000 inches
Fork Load Center Distance:
24.000 inches
Fork/platform Maximum Free Lift Height:
57.000 inches
57.000 inches
57.000 inches  Lift Mechanism Type:
57.000 inches  Lift Mechanism Type:  Hydraulic
57.000 inches  Lift Mechanism Type:  Hydraulic  Lift Actuation Method:
57.000 inches  Lift Mechanism Type:  Hydraulic  Lift Actuation Method:  Powered
57.000 inches  Lift Mechanism Type: Hydraulic  Lift Actuation Method: Powered  Prime Mover Type:
57.000 inches  Lift Mechanism Type: Hydraulic  Lift Actuation Method: Powered  Prime Mover Type: Electric motor
57.000 inches  Lift Mechanism Type: Hydraulic  Lift Actuation Method: Powered  Prime Mover Type: Electric motor  Maximum Load Rating:
57.000 inches  Lift Mechanism Type: Hydraulic  Lift Actuation Method: Powered  Prime Mover Type: Electric motor  Maximum Load Rating: 4000.000 pounds
57.000 inches  Lift Mechanism Type: Hydraulic  Lift Actuation Method: Powered  Prime Mover Type: Electric motor  Maximum Load Rating: 4000.000 pounds  Features Provided:
57.000 inches  Lift Mechanism Type: Hydraulic Lift Actuation Method: Powered Prime Mover Type: Electric motor Maximum Load Rating: 4000.000 pounds Features Provided: Telescopic mast
57.000 inches  Lift Mechanism Type: Hydraulic  Lift Actuation Method: Powered  Prime Mover Type: Electric motor  Maximum Load Rating: 4000.000 pounds  Features Provided: Telescopic mast  Wheel Type And Quantity:
57.000 inches  Lift Mechanism Type: Hydraulic  Lift Actuation Method: Powered  Prime Mover Type: Electric motor  Maximum Load Rating: 4000.000 pounds  Features Provided: Telescopic mast  Wheel Type And Quantity: 2 dual solid steerable wheel
57.000 inches  Lift Mechanism Type: Hydraulic  Lift Actuation Method: Powered  Prime Mover Type: Electric motor  Maximum Load Rating: 4000.000 pounds  Features Provided: Telescopic mast  Wheel Type And Quantity: 2 dual solid steerable wheel  Lift Height Of Forks:
57.000 inches  Lift Mechanism Type: Hydraulic  Lift Actuation Method: Powered  Prime Mover Type: Electric motor  Maximum Load Rating: 4000.000 pounds  Features Provided: Telescopic mast  Wheel Type And Quantity: 2 dual solid steerable wheel  Lift Height Of Forks: 144.000 inches
57.000 inches  Lift Mechanism Type: Hydraulic  Lift Actuation Method: Powered  Prime Mover Type: Electric motor  Maximum Load Rating: 4000.000 pounds  Features Provided: Telescopic mast  Wheel Type And Quantity: 2 dual solid steerable wheel Lift Height Of Forks: 144.000 inches  Boom Forward Tilt Angle:

## **NSN 3930-00-965-0140**Fork Lift Truck - Page 2 of 2



Fork Spread Distance:
Between 12.000 inches and 32.000 inches
Special Features:
Upright boom
Style Designator:
Conventional
Specification Or Standard:
E type and v size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A085a0