Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3930-01-163-0842

Body Material: Steel Mounting Provision: Pin Mounting Facility Length: 2.250 inches Bore Diameter: 1.250 inches Overall Diameter: 2.642 inches
Mounting Provision: Pin Mounting Facility Length: 2.250 inches Bore Diameter: 1.250 inches Overall Diameter:
Pin Mounting Facility Length: 2.250 inches Bore Diameter: 1.250 inches Overall Diameter:
Mounting Facility Length: 2.250 inches Bore Diameter: 1.250 inches Overall Diameter:
2.250 inches Bore Diameter: 1.250 inches Overall Diameter:
Bore Diameter: 1.250 inches Overall Diameter:
1.250 inches Overall Diameter:
Overall Diameter:
2.642 inches
End Application:
Hyster co truck lift models w40bf, w60bf, w40bl, w60bl and t5b
First End Hole Diameter:
0.745 inches
Compressed Length:
17.250 inches
Extended Length:
26.500 inches
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Double acting single cylinder
First Piston Rod End Style:
Fork type (clevis)
First End Largest Inside Diameter:
0.745 inches
First End Fork Width:
1.735 inches
First End Fork Depth:
2.040 inches
First End Fork Span Width:
0.882 inches
Mounting Type And Location:
Fork cylinder head end
Mounting Facility Diameter:
0.712 inches
Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Unf



Port Thread Diameter:

0.438 inches

Port Thready Qty Per Inch (tpi):

20

Port Thread Class:

3b

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A34200