NSN 3940-00-051-8600

Tackle Block - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3940-00-051-8600

Bearing Type:
Plain
Maximum Load Rating:
3300.0 pounds
Block Type:
Regular
Sheave Quantity:
1
Tackle Accommodated Type:
Fibrous rope
Becket Type:
Thimble
Antitoppling Device:
Not included
Shell Length:
8.000 inches
Sheave Outside Diameter:
4.500 inches
Center Pin Diameter:
0.625 inches
Becket Quantity:
1
Sheave Bearing Lubrication Method:
oneave bearing Eubrication Method.
Self-lubricated
_
Self-lubricated
Self-lubricated Maximum Tackle Diameter Accommodated:
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device:
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included Attachment Style:
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included Attachment Style: Jaw and eye swivel
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included Attachment Style: Jaw and eye swivel Material And Location:
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included Attachment Style: Jaw and eye swivel Material And Location: Steel center pin
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included Attachment Style: Jaw and eye swivel Material And Location: Steel center pin Surface Treatment And Location:
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included Attachment Style: Jaw and eye swivel Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included Attachment Style: Jaw and eye swivel Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic Special Features:
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included Attachment Style: Jaw and eye swivel Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.375 in.
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included Attachment Style: Jaw and eye swivel Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.375 in. Style Designator:
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included Attachment Style: Jaw and eye swivel Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.375 in. Style Designator: Round pattern
Self-lubricated Maximum Tackle Diameter Accommodated: 1.000 inches Tackle Locking Device: Not included Attachment Style: Jaw and eye swivel Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.375 in. Style Designator: Round pattern Specification Or Standard:

NSN 3940-00-051-8600 Tackle Block - Page 2 of 2



	Of			

Demilitarization:

No

Fiig:

A12900