NSN 3940-00-059-5996

Tackle Block - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3940-00-059-5996

Bearing Type:
Plain
Maximum Load Rating:
3300.0 pounds
Block Type:
Regular
Sheave Quantity:
2
Tackle Accommodated Type:
Fibrous rope
Becket Type:
Thimble
Antitoppling Device:
Not included
Shell Length:
6.000 inches
Sheave Outside Diameter:
3.500 inches
Center Pin Diameter:
0.500 inches
Becket Quantity:
1
Sheave Bearing Lubrication Method:
Sheave Bearing Lubrication Method:
Sheave Bearing Lubrication Method: Self-lubricated
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included Attachment Style:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included Attachment Style: Flatted loose swivel eye with swivel hook
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included Attachment Style: Flatted loose swivel eye with swivel hook Material And Location:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included Attachment Style: Flatted loose swivel eye with swivel hook Material And Location: Steel center pin
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included Attachment Style: Flatted loose swivel eye with swivel hook Material And Location: Steel center pin Surface Treatment And Location:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included Attachment Style: Flatted loose swivel eye with swivel hook Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included Attachment Style: Flatted loose swivel eye with swivel hook Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic Special Features:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included Attachment Style: Flatted loose swivel eye with swivel hook Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.000 in.
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included Attachment Style: Flatted loose swivel eye with swivel hook Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.000 in. Style Designator:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included Attachment Style: Flatted loose swivel eye with swivel hook Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.000 in. Style Designator: Round pattern
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 0.750 inches Tackle Locking Device: Not included Attachment Style: Flatted loose swivel eye with swivel hook Material And Location: Steel center pin Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.000 in. Style Designator: Round pattern Specification Or Standard:

NSN 3940-00-059-5996

Tackle Block - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A12900