## NSN 3940-00-865-8708

Tackle Block - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3940-00-865-8708

| Bearing Type:                         |
|---------------------------------------|
| Plain                                 |
| Maximum Load Rating:                  |
| 3300.0 pounds                         |
| Block Type:                           |
| Regular                               |
| Sheave Quantity:                      |
| 1                                     |
| Tackle Accommodated Type:             |
| Fibrous rope                          |
| Becket Type:                          |
| Thimble                               |
| Antitoppling Device:                  |
| Not included                          |
| Shell Length:                         |
| 8.000 inches                          |
| Sheave Outside Diameter:              |
| 4.500 inches                          |
| Center Pin Diameter:                  |
| 0.625 inches                          |
| Becket Quantity:                      |
| 1                                     |
| Sheave Bearing Lubrication Method:    |
| Self-lubricated                       |
| Maximum Tackle Diameter Accommodated: |
| 1.000 inches                          |
| Tackle Locking Device:                |
| Not included                          |
| Attachment Style:                     |
| Upset shackle in shackle              |
| Material And Location:                |
| Steel shell err-100 err-100           |
| Surface Treatment And Location:       |
| Zinc, electrolytic                    |
| Special Features:                     |
| Sheave thickness at rim min 1.375 in. |
| Style Designator:                     |
| Round pattern                         |
| Shelf Life:                           |
| N/a                                   |
| Unit Of Measure:                      |

--

## NSN 3940-00-865-8708

Tackle Block - Page 2 of 2



Demilitarization:

No

Fiig:

A12900