## NSN 3940-00-892-4559

Tackle Block - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3940-00-892-4559

Bearing Type:
Plain
Maximum Load Rating:
10000.0 pounds
Block Type:
Regular
Sheave Quantity:
3
Tackle Accommodated Type:
Fibrous rope
Becket Type:
Thimble
Antitoppling Device:
Not included
Shell Length:
10.000 inches
Sheave Outside Diameter:
6.250 inches
Center Pin Diameter:
0.750 inches
Becket Quantity:
4
1
Sheave Bearing Lubrication Method:
·
Sheave Bearing Lubrication Method:
Sheave Bearing Lubrication Method: Self-lubricated
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 1.250 inches
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included Attachment Style:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included Attachment Style: Chain shackle
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included Attachment Style: Chain shackle Material And Location:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included Attachment Style: Chain shackle Material And Location: Steel center pin err-100 err-100
Sheave Bearing Lubrication Method: Self-lubricated  Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included Attachment Style: Chain shackle Material And Location: Steel center pin err-100 err-100 Surface Treatment And Location:
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included Attachment Style: Chain shackle Material And Location: Steel center pin err-100 err-100 Surface Treatment And Location: Zinc, electrolytic
Sheave Bearing Lubrication Method: Self-lubricated  Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included Attachment Style: Chain shackle Material And Location: Steel center pin err-100 err-100 Surface Treatment And Location: Zinc, electrolytic Special Features:
Sheave Bearing Lubrication Method: Self-lubricated  Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included Attachment Style: Chain shackle Material And Location: Steel center pin err-100 err-100 Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.500 in.
Sheave Bearing Lubrication Method: Self-lubricated Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included Attachment Style: Chain shackle Material And Location: Steel center pin err-100 err-100 Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.500 in. Style Designator:
Sheave Bearing Lubrication Method: Self-lubricated  Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included Attachment Style: Chain shackle Material And Location: Steel center pin err-100 err-100 Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.500 in. Style Designator: Round pattern
Sheave Bearing Lubrication Method: Self-lubricated  Maximum Tackle Diameter Accommodated: 1.250 inches Tackle Locking Device: Not included Attachment Style: Chain shackle Material And Location: Steel center pin err-100 err-100 Surface Treatment And Location: Zinc, electrolytic Special Features: Sheave thickness at rim min 1.500 in. Style Designator: Round pattern Specification Or Standard:

## NSN 3940-00-892-4559

Tackle Block - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A12900