## NSN 3940-00-988-4661

Tackle Block - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3940-00-988-4661

Bearing Type:

Bearing Type:
Plain
Maximum Load Rating:
2000.0 pounds
Block Type:
Regular
Sheave Quantity:
3
Tackle Accommodated Type:
Fibrous rope
Antitoppling Device:
Not included
Shell Length:
4.000 inches
Sheave Outside Diameter:
2.250 inches
Center Pin Diameter:
0.375 inches
Sheave Bearing Lubrication Method:
Self-lubricated
Maximum Tackle Diameter Accommodated:
Maximum Tackle Diameter Accommodated: 0.500 inches
0.500 inches
0.500 inches  Tackle Locking Device:
0.500 inches  Tackle Locking Device:  Not included
0.500 inches  Tackle Locking Device:  Not included  Attachment Style:
0.500 inches  Tackle Locking Device:  Not included  Attachment Style:  Loose side single side
0.500 inches  Tackle Locking Device:  Not included  Attachment Style:  Loose side single side  Material And Location:
0.500 inches  Tackle Locking Device:  Not included  Attachment Style:  Loose side single side  Material And Location:  Steel center pin err-100 err-100
0.500 inches  Tackle Locking Device:  Not included  Attachment Style:  Loose side single side  Material And Location:  Steel center pin err-100 err-100  Surface Treatment And Location:
0.500 inches  Tackle Locking Device:  Not included  Attachment Style:  Loose side single side  Material And Location:  Steel center pin err-100 err-100  Surface Treatment And Location:  Zinc, astm a153 sheave
0.500 inches  Tackle Locking Device:  Not included  Attachment Style:  Loose side single side  Material And Location:  Steel center pin err-100 err-100  Surface Treatment And Location:  Zinc, astm a153 sheave  Style Designator:
0.500 inches  Tackle Locking Device:  Not included  Attachment Style:  Loose side single side  Material And Location:  Steel center pin err-100 err-100  Surface Treatment And Location:  Zinc, astm a153 sheave  Style Designator:  Oval pattern
O.500 inches  Tackle Locking Device:  Not included  Attachment Style:  Loose side single side  Material And Location:  Steel center pin err-100 err-100  Surface Treatment And Location:  Zinc, astm a153 sheave  Style Designator:  Oval pattern  Departure From Cited Designator:
O.500 inches  Tackle Locking Device:  Not included  Attachment Style:  Loose side single side  Material And Location:  Steel center pin err-100 err-100  Surface Treatment And Location:  Zinc, astm a153 sheave  Style Designator:  Oval pattern  Departure From Cited Designator:  As modified by pacs amdb and amxf
O.500 inches  Tackle Locking Device:  Not included  Attachment Style: Loose side single side  Material And Location: Steel center pin err-100 err-100  Surface Treatment And Location: Zinc, astm a153 sheave  Style Designator: Oval pattern  Departure From Cited Designator: As modified by pacs amdb and amxf  Shelf Life:
O.500 inches  Tackle Locking Device:  Not included  Attachment Style: Loose side single side  Material And Location: Steel center pin err-100 err-100  Surface Treatment And Location: Zinc, astm a153 sheave  Style Designator: Oval pattern  Departure From Cited Designator: As modified by pacs amdb and amxf  Shelf Life: N/a
O.500 inches  Tackle Locking Device:  Not included  Attachment Style: Loose side single side  Material And Location: Steel center pin err-100 err-100  Surface Treatment And Location: Zinc, astm a153 sheave  Style Designator: Oval pattern  Departure From Cited Designator: As modified by pacs amdb and amxf  Shelf Life: N/a

Fiig:

A12900