NSN 3940-01-311-2876

Multiple Leg Sling - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3940-01-311-2876

Design Type: Multiple leg Leg Length And Quantity: 1 leg 26 in.; 1 leg 46 in.; 1 leg 47 in. Sling Spreader: Not included Common Attachment Guide Rope: Not included Sling Material Type: Wire rope Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matt tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Design Type: Multiple leg Leg Length And Quantity: 1 leg 26 in.; 1 leg 46 in.; 1 leg 47 in. Sling Spreader: Not included Common Attachment Guide Rope: Not included Sling Material Type: Wire rope Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Cross Section Outside Diameter:
Multiple leg Leg Length And Quantity: 1 leg 26 in.; 1 leg 46 in.; 1 leg 47 in. Sling Spreader: Not included Common Attachment Guide Rope: Not included Sling Material Type: Wire rope Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.188 inches
Leg Length And Quantity: 1 leg 26 in.; 1 leg 46 in.; 1 leg 47 in. Sling Spreader: Not included Common Attachment Guide Rope: Not included Sling Material Type: Wire rope Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Design Type:
1 leg 26 in.; 1 leg 46 in.; 1 leg 47 in. Sting Spreader: Not included Common Attachment Guide Rope: Not included Sling Material Type: Wire rope Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Multiple leg
Sling Spreader: Not included Common Attachment Guide Rope: Not included Sling Material Type: Wire rope Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Leg Length And Quantity:
Not included Common Attachment Guide Rope: Not included Sling Material Type: Wire rope Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1 leg 26 in.; 1 leg 46 in.; 1 leg 47 in.
Common Attachment Guide Rope: Not included Sling Material Type: Wire rope Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Sling Spreader:
Not included Sling Material Type: Wire rope Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not included
Sling Material Type: Wire rope Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Common Attachment Guide Rope:
Wire rope Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not included
Special Features: Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Sling Material Type:
Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Wire rope
window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coate steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in. Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rqrd to remove and install windshields and fixed windows currently used on dc-10/kc-10; windshield wt 137 lbs, 25 in. Ht by 40 in. Wd; fixed
Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	window wt 85 lbs, 34 in. Ht by 33 in. Lg; sling used in conjunction w/mounted jib crane, p/n 60001 and serd 010022; wire rope matl tin coated
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	steel; cable connected to fittings by thimble and sleeve assembly; link has opening 6 in. Long and 1.5 in. Radius at larger end and .75 in.
N/a Unit Of Measure: Demilitarization: No Fiig:	Radius at smaller end; sling fittings bolt to window hoist points after dummy bolts have been removed; cad plated finish; wt 7 lbs
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	-
Fiig:	Demilitarization:
-	No
T215 a	Fiig:
1210 - 9	T215-g