NSN 3940-01-339-6213

Hoisting Adapter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3940-01-339-6213

Attachment Method: Eye Overall Diameter: Between 4.730 inches and 4.770 inches End Application: Pacer dawn Usage Design: Rotor Special Features: Thickness 0.36 min 0.40 maximum at od; with 16 holes 0.341 min 0.350 maximum equally spaced on a 4.00 basic dia; eye bol center for lifting; eyebolt pn 89-023 cage 03914; proof test 250 lbs Material: Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life: N/a	
Overall Diameter: Between 4.730 inches and 4.770 inches End Application: Pacer dawn Usage Design: Rotor Special Features: Thickness 0.36 min 0.40 maximum at od; with 16 holes 0.341 min 0.350 maximum equally spaced on a 4.00 basic dia; eye bol center for lifting; eyebolt pn 89-023 cage 03914; proof test 250 lbs Material: Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
Between 4.730 inches and 4.770 inches End Application: Pacer dawn Usage Design: Rotor Special Features: Thickness 0.36 min 0.40 maximum at od; with 16 holes 0.341 min 0.350 maximum equally spaced on a 4.00 basic dia; eye bol center for lifting; eyebolt pn 89-023 cage 03914; proof test 250 lbs Material: Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
End Application: Pacer dawn Usage Design: Rotor Special Features: Thickness 0.36 min 0.40 maximum at od; with 16 holes 0.341 min 0.350 maximum equally spaced on a 4.00 basic dia; eye bol center for lifting; eyebolt pn 89-023 cage 03914; proof test 250 lbs Material: Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
Pacer dawn Usage Design: Rotor Special Features: Thickness 0.36 min 0.40 maximum at od; with 16 holes 0.341 min 0.350 maximum equally spaced on a 4.00 basic dia; eye bol center for lifting; eyebolt pn 89-023 cage 03914; proof test 250 lbs Material: Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
Usage Design: Rotor Special Features: Thickness 0.36 min 0.40 maximum at od; with 16 holes 0.341 min 0.350 maximum equally spaced on a 4.00 basic dia; eye bol center for lifting; eyebolt pn 89-023 cage 03914; proof test 250 lbs Material: Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
Rotor Special Features: Thickness 0.36 min 0.40 maximum at od; with 16 holes 0.341 min 0.350 maximum equally spaced on a 4.00 basic dia; eye bol center for lifting; eyebolt pn 89-023 cage 03914; proof test 250 lbs Material: Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
Special Features: Thickness 0.36 min 0.40 maximum at od; with 16 holes 0.341 min 0.350 maximum equally spaced on a 4.00 basic dia; eye bol center for lifting; eyebolt pn 89-023 cage 03914; proof test 250 lbs Material: Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
Thickness 0.36 min 0.40 maximum at od; with 16 holes 0.341 min 0.350 maximum equally spaced on a 4.00 basic dia; eye bol center for lifting; eyebolt pn 89-023 cage 03914; proof test 250 lbs Material: Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
center for lifting; eyebolt pn 89-023 cage 03914; proof test 250 lbs Material: Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
Material: Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	located i
Steel, qq-s-763, class 304 or steel, qq-s-763, class 347 Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
Material: Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
Steel comp 304 or steel comp 347 Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
Material Specification: Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res Shelf Life:	
Qq-s-763, class 304 federal specification 1st material response and qq-s-763, class 347 federal specification 2nd material res	
Shelf Life:	
	onse
N/a	
IVa	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A30600	