

View Online at <https://aerobasegroup.com/nsn/3950-00-025-9931>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller

Environmental Protection:

Any acceptable

Maximum Lift Height:

18.0 feet

Flange Width:

6.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Duty Cycle:

Intermittent

Operation Method:

Power

Load Limit At Selected Speed And Drum Location:

4000.0 pounds single speed first drum

Travel Rate Per Minute:

30.0 feet

Mechanical Advantage Method:

Spur gear

Braking Method:

Electric

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

4.00 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, standard i beam, wheels vertical

Trolley Type:

Hand geared

Track Height:

10.000 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

22.000 inches

Mounting Position:

Parallel

Cooling Method:

Self-ventilated

Voltage In Volts:

208.0

Phase:

Three

Frequency In Hertz:

60.0

Specification Or Standard:

1 type and c class and 1 speed and 2 ton capacity rating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800