

View Online at <https://aerobasegroup.com/nsn/3950-00-028-6717>

Prime Mover Quantity:

1

Current Type:

Dc

Furnished Items And Quantity:

1 motor controller and 1 pawl and ratchet

Environmental Protection:

Waterproof

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Drum Flange To Flange Distance And Location:

18.000 inches first drum and 18.000 inches second drum

Drum Diameter And Location:

18.000 inches first drum and 18.000 inches second drum

Drum Flange Diameter And Location:

30.000 inches first drum and 30.000 inches second drum

Capstan Spool Mounting Position:

Horizontal

Capstan Spool Style:

Single head

Capstan Spool Surface Design:

Plain

Capstan Spool Quantity:

2

Load Limit At Selected Speed And Drum Location:

3700.0 pounds single speed first drum and 3700.0 pounds single speed second drum

Travel Rate Per Minute:

220.0 feet

Braking Method:

Manual

Clutch Type:

Friction

Power Requirement Rating:

50.00 horsepower

Drum Surface Design:

Plain

Largest Diameter And Location:

15.000 inches first spool and 15.000 inches second spool

Overall Length And Location:

12.438 inches first spool and 12.438 inches second spool

Cooling Method:

Any acceptable

Voltage In Volts:

230.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800