

View Online at <https://aerobasegroup.com/nsn/3950-00-089-5741>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller

Environmental Protection:

Splashtight

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Drum Flange To Flange Distance And Location:

15.000 inches first drum

Drum Diameter And Location:

24.000 inches first drum

Drum Flange Diameter And Location:

37.000 inches first drum

Capstan Spool Mounting Position:

Horizontal

Capstan Spool Style:

Single head

Capstan Spool Surface Design:

Plain

Capstan Spool Quantity:

2

Load Limit At Selected Speed And Drum Location:

6000.0 pounds single speed first drum and 3000.0 pounds second speed first drum

Travel Rate Per Minute:

250.00 feet and 500.00 feet

Braking Method:

Manual

Clutch Type:

Friction

Power Requirement Rating:

75.00 horsepower

Drum Surface Design:

Grooved

Transmission Type:

Manual

Cooling Method:

Any acceptable

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

With gypsy head

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800