

View Online at <https://aerobasegroup.com/nsn/3950-00-138-3825>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 remote control and 2 wire rope

Environmental Protection:

Any acceptable

Maximum Lift Height:

25.0 feet

Flange Width:

6.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Continuous

Operation Method:

Powered

Travel Rate Per Minute:

32.0 feet

Braking Method:

Electric

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

1.000 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, standard i beam, wheels vertical

Trolley Type:

Plain

Track Height:

15.000 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

23.250 inches

Wheel Center To Center Distance:

13.125 inches

Maximum Load Rating:

1000.0 pounds

Mounting Position:

Parallel

Cooling Method:

Blower cooled

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

0.250 in. Diameter wire rope

Frequency In Hertz:

60.0

Supplementary Features:

Hoist motor is open drip proof not rated for outdoor service

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800