

View Online at <https://aerobasegroup.com/nsn/3950-00-138-3825>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 remote control and 2 wire rope

**Environmental Protection:**

Any acceptable

**Maximum Lift Height:**

25.0 feet

**Flange Width:**

6.000 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Continuous

**Operation Method:**

Powered

**Travel Rate Per Minute:**

32.0 feet

**Braking Method:**

Electric

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

1.000 horsepower

**Suspension Mounting Method:**

Trolley

**Trolley Suspension Style:**

Plain, standard i beam, wheels vertical

**Trolley Type:**

Plain

**Track Height:**

15.000 inches

**Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:**

23.250 inches

**Wheel Center To Center Distance:**

13.125 inches

**Maximum Load Rating:**

1000.0 pounds

**Mounting Position:**

Parallel

**Cooling Method:**

Blower cooled

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Special Features:**

0.250 in. Diameter wire rope

**Frequency In Hertz:**

60.0

**Supplementary Features:**

Hoist motor is open drip proof not rated for outdoor service

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800