

View Online at <https://aerobasegroup.com/nsn/3950-00-141-7193>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Fungus resistant

**Maximum Lift Height:**

20.0 feet

**Flange Width:**

Between 3.330 inches and 4.660 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

Any acceptable

**Suspension Mounting Method:**

Trolley

**Trolley Suspension Style:**

Plain, standard i beam, wheels vertical

**Trolley Type:**

Plain

**Track Height:**

Any acceptable

**Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:**

25.000 inches

**Wheel Center To Center Distance:**

Any acceptable

**Mounting Position:**

Any acceptable

**Cooling Method:**

Any acceptable

**Voltage In Volts:**

220.0

**Phase:**

Three

**Special Features:**

Spur gear type; 2 or 4 load ropes; 1000.0 lbs load capacity; 17.0 to 18.0 ft h of lift; 20.0 to 24.0 ft per minute hoisting speed

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800