

View Online at <https://aerobasegroup.com/nsn/3950-00-141-7193>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Fungus resistant

Maximum Lift Height:

20.0 feet

Flange Width:

Between 3.330 inches and 4.660 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

Any acceptable

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, standard i beam, wheels vertical

Trolley Type:

Plain

Track Height:

Any acceptable

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

25.000 inches

Wheel Center To Center Distance:

Any acceptable

Mounting Position:

Any acceptable

Cooling Method:

Any acceptable

Voltage In Volts:

220.0

Phase:

Three

Special Features:

Spur gear type; 2 or 4 load ropes; 1000.0 lbs load capacity; 17.0 to 18.0 ft h of lift; 20.0 to 24.0 ft per minute hoisting speed

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800