NSN 3950-00-188-3368

Capstan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3950-00-188-3368

| Prime Mover Quantity: |
|--|
| 1 |
| Current Type: |
| Dc |
| Furnished Items And Quantity: |
| 1 motor controller |
| Environmental Protection: |
| Dripproof |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Duty Cycle: |
| Intermittent |
| Operation Method: |
| Power |
| Capstan Spool Mounting Position: |
| Vertical |
| Capstan Spool Surface Design: |
| Plain |
| Capstan Spool Quantity: |
| 1 |
| Load Limit At Selected Speed And Drum Location: |
| 15000.0 pounds single speed first drum |
| Travel Rate Per Minute: |
| 50.0 feet |
| Braking Method: |
| Electric |
| Power Requirement Rating: |
| 35.00 horsepower |
| Largest Diameter And Location: |
| 30.000 inches first spool |
| Overall Length And Location: |
| 27.375 inches first spool |
| Cooling Method: |
| Any acceptable |
| Voltage In Volts: |
| voltage in volta. |
| 115.0 |
| |
| 115.0 |
| 115.0 Reference Number Differentiating Characteristics: |

NSN 3950-00-188-3368

Capstan - Page 2 of 2



| | • • | | | | | |
|----|-----|-------------|----|----|-----|----|
| ın | 18 | <i>(</i>)+ | Me | 20 | III | ω. |
| | | | | | | |

--

Demilitarization:

No

Fiig:

A02800