

View Online at <https://aerobasegroup.com/nsn/3950-00-193-3562>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Any acceptable

Maximum Lift Height:

20.0 feet

Chain Type:

Proof coil

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Load Limit At Selected Speed And Drum Location:

1000.0 pounds single speed first drum

Travel Rate Per Minute:

8.0 feet

Mechanical Advantage Method:

Multiple gear

Braking Method:

Automatic

Hook Quantity:

1

Load Element Quantity Per Hook:

2

Center To Center Distance Between Load Elements:

Any acceptable

Power Requirement Rating:

0.25 horsepower

Suspension Mounting Method:

Hook

Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:

22.000 inches

Chain Material Diameter:

Any acceptable

Mounting Position:

Swivel

Cooling Method:

Any acceptable

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Special Features:

Push-button pendant control; weight 65.0 pounds; 30 minutes 55.0 degrees c temperature rise; all hooks w/safety latches, nongovernment document data: hmi400-18878

Frequency In Hertz:

60.0

Nongovernment Document Data:

Hmi400-18878

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800