

View Online at <https://aerobasegroup.com/nsn/3950-00-193-3562>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Any acceptable

**Maximum Lift Height:**

20.0 feet

**Chain Type:**

Proof coil

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Load Limit At Selected Speed And Drum Location:**

1000.0 pounds single speed first drum

**Travel Rate Per Minute:**

8.0 feet

**Mechanical Advantage Method:**

Multiple gear

**Braking Method:**

Automatic

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

2

**Center To Center Distance Between Load Elements:**

Any acceptable

**Power Requirement Rating:**

0.25 horsepower

**Suspension Mounting Method:**

Hook

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

22.000 inches

**Chain Material Diameter:**

Any acceptable

**Mounting Position:**

Swivel

**Cooling Method:**

Any acceptable

**Voltage In Volts:**

115.0 and 230.0

**Phase:**

Single

**Special Features:**

Push-button pendant control; weight 65.0 pounds; 30 minutes 55.0 degrees c temperature rise; all hooks w/safety latches, nongovernment document data: hmi400-18878

**Frequency In Hertz:**

60.0

**Nongovernment Document Data:**

Hmi400-18878

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800